



novoSchwank L

CALEFACTOR RADIANTE INFRARROJO BAJA INTENSIDAD

FICHA TÉCNICA

DIMENSIONES (mm)		20S L	25S L	35S L	45S L	55S L
LARGO QUEMADOR		445	445	445	445	470
LARGO TUBO RADIANTE		6.100	6.100	9.150	12.200	13.620
LARGO TOTAL		6.545	6.545	9.595	12.645	14.090

		GAS				
GAS NAT H / G 20	GAS INPUT - BRUTO (kW)	16,7	21,1	32,2	43,3	54,4
	GAS INPUT - NETO (kW)	15,0	19,0	29,0	39,0	49,0
	CONSUMO DE GAS (m³/h)	1,50	1,91	2,91	3,91	4,91
PROPANO / G 31	GAS INPUT - BRUTO (kW)	16,4	20,4	31,6	42,5	53,4
	GAS INPUT - NETO (kW)	15,0	19,0	29,0	39,0	49,0
	CONSUMO DE GAS (m³/h)	1,17	1,48	2,25	3,03	3,81

PESO EN KG	56	56	79	102	125
CONEXIÓN AIRE/SALIDA DE GASES	Ø100				
CONSUMO ELÉCTRICO EN W	104	104	104	104	91
CONEXIÓN A GAS	R1/2"	R1/2"	R1/2"	R3/4"	R3/4"
SUMINISTRO ELÉCTRICO	230 V / 50 Hz ~				
IGNICIÓN Y CONTROL	IGNICIÓN POR BUJÍAS Y ELECTRODO DE IONIZACIÓN POR CONTROL AUTOMÁTICO				

→ APLICACIONES

Calefacción de pasillos, carpas, obras de construcción.



Schwank
Heating. Design. Comfort.



Contáctanos